



Series	AGM-R	Warranty	See Warranty Terms
Volts	12	BCI	
Terminal Type		F14(M8)	
Included Hardware		M8 stainless bolts & washers	
Size & Thread		M8	

### Charge

Charge Voltage Range	14.7V @ 25°C (77°F)
Float Voltage Range	13.8V @ 25°C (77°F)
Recommended Charge Current	35 A
Maximum Charge Current	55 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	4 mΩ

### Capacity

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 20 Hour Rate	<b>196 AH</b>	<b>9.8 A</b>
@ 10 Hour Rate	<b>185 AH</b>	<b>18.5 A</b>
@ 5 Hour Rate	<b>157 AH</b>	<b>31.4 A</b>

Cut Off Voltage	Constant Current Discharge						
	1 hr	2 hr	3 hr	4 hr	5 hr	8 hr	10 hr
1.8 VPC	97.9	58.7	46.3	36.7	31.4	22.1	18.5


### Specifications

	Weight	54 kg	119 lbs
	Length	56.0 cm	22.1"
	Width	12.5 cm	4.92"
	Height Inc. Term.	31.6 cm	12.4"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Rope / Plastic Handle

### Cycle Life vs. Depth of Discharge



### Detailed Illustration

