



Series	R-Series LFP	Warranty	See Warranty Terms
Volts	36	BCI	4D
Terminal Type	M8		
Included Hardware	M8 stainless bolts & washers		

Charge

Charge Voltage Range	42.0 - 43.8V	
Recommended End of Discharge Voltage	36.0 V	
End of Discharge Protection Voltage	30.0 V	
Recommended Charge Voltage	43.2 V	
Recommended Charge Current		
0~10°C (32-50°F)	0.2C	24A
10~35°C (50-95°F)	0.5C	60A
35~50°C (95-122°F)	0.2C	24A

Charge Mode:

- Charge at recommend voltage & current by temperature until charge current drops to $\leq 0.05C$ (CC,CV)
- DO NOT USE TEMPERATURE COMPENSATION
- No BTS (Battery Temperature Sensor)

Max Continuous Charge Current	60 A
Max Continuous Discharge Current	100 A
Surge Current Limit	700 A (300ms)
Charge Temperature Range	0°C~55°C (32~131°F)
Discharge Temperature Range	-20°~60°C (-4~140°F)
Storage Temperature Range	-5°~45°C (23~113°F)

Capacity

Nominal Capacity	120 AH
Total Energy	3.84 kWh
Nominal Voltage	38.4 V

Safety

- Cylindrical LiFePO4 cells (UL1642)
- IEC62133 (cell), IEC62619(cell), UN38.3 (cell/pack)
- ROHS (cell), CE system certification, IP65 Rating

Design

- Standard-size (BCI) ABS container for easy VRLA replacement
- Fast charge/discharge performance
- Maintenance-free operation
- Bluetooth Connectivity & dedicated IOS & Android App

Battery Management System (BMS)

- Integrated hardware BMS inside
- Independent charge & discharge protection
- Short-Circuit Protection, Over-Voltage Protection, Low-Voltage Protection, Over-Curent Protection, Low-Temperature Protection, Over-Temperature Protection

36V LFP Profile


Specifications

	Weight	33 kg	72.6 lbs
	Length	52.1 cm	20.5"
	Width	23.8 cm	9.37"
	Height Inc. Term.	22.1 cm	8.7"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Rope / Plastic Handle
Internal BMS Model	12S100A
Expected Cycle Life	>6000 @ 80% DOD, >3000 @ 100% DOD
Series Connection	1 UNITS MAX
Parallel Connection	6 UNITS MAX

Detailed Illustration



ISO9001



ISO14001



OHSAS18001

