



Series	GEL	Warranty	See Warranty Terms
Volts	2	BCI	2V OPzV
Cells	1		
Terminal Type	F10		
Included Hardware	Threaded Insert & Bolt		

Charge

Recommended Charge Current	42 A
Maximum Charge Current	126 A
Self-Discharge Rate	Less than 2% per month at 20°C (68°F)
Internal Resistance	0.6 mΩ

Capacity

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	89%	79%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	668 AH	6.68 A
@ 20 Hour Rate	551 AH	27.55 A
@ 10 Hour Rate	486 AH	48.6 A

Specifications




Weight	35 kg	77 lbs
Length	14.5 cm	5.71"
Width	20.6 cm	8.11"
Height Inc. Term.	49.8 cm	19.61"


Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	None

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature



ISO 9001



ISO 14001



OHSAS 18001



MH 28539

